

## **TEAM SERIES – IDV/PB**

Recommended for small stores, fields and tournaments.

### **General Specifications and Standard Features**

- 5000 PSIG Maximum Operating Pressure
  - 4.7 to 7 SCFM Free Air Delivery
  - 5.6 to 8.4 SCFM Charging Rate
  - 3-Stage Continuous-Duty Rated Compressor
  - Air-Cooled
  - Pressure Lubricated with Oil Filter
  - Air Processing System with Replaceable Cartridge
  - Attended Manual Operation
- 
- Inlet Filter
  - Stainless Steel Interstage Coolers
  - Stainless Steel Aftercooler
  - Corrosion Resistant Interstage Separator with Manual Drain
  - Corrosion Resistant Final Separator with Manual Drain
  - Interstage Safety Valves
  - Final Safety Valve
  - Pressure Maintaining Valve
  - Check Valve
  - V-Belt Drive with Guard
  - Cooling Fan with Guard
  - Vibration Isolators
  - Powder Coated Finish
  - 5-Ft Fill Hose with Pressure Gauge, Venting Valve and CGA 347 Connector

#### Disclaimers:

Capacity is referenced to standard inlet conditions and 80% of the compressor's maximum operating pressure.

Tolerance on capacity is +/- 5%.

1 Year Warranty.

Ambient Temperature Range: +40 to +113 °F

Dimensions and weight are approximate.

Use only with a suitable protected electric outlet installed by a licensed electrician.

Use gasoline engine only in a well ventilated area.

IDV/PB is recommended for filling up to four or more storage cylinders.

IDV/PB is recommended for tournament air supply with low volume air requirement.

IDV/PB is not recommended for filling paintball marker tanks directly.

Consult BAUER for sizing.

All information is subject to change without notice or obligation.